

The Experts in Packaging Systems

Engineered Systems | Innovative Machines | Excellent Quality Bags

MAX 12^m & MAX 20^m

Continuous Roll Bagging System





Standard for All of **Sharp's Machines**

Total Systems Care

Maintenance Program for **Sharp Machines**

- Installation and training
- Free replacement parts for one year
- Two preventive maintenance visits
- Free telephone technical support
- Discounted labor rates
- Preferred service scheduling
- Trade-in incentives for machinery





Engineering Expertise to Customize Your Systems

Sharp Packaging System's Engineering Group provides the most cost effective, productive, and reliable integration available. We have a team of software and mechanical engineers to develop the best possible packaging system, customized for your needs.

Hands-on assistance

We offer complete integration and automation and will assist at each step of the process, from research to design, installation, and training. Once your system is installed, Sharp engineers are available for support and help with troubleshooting.

Maximize speed and uptime

With cutting edge engineering tools, such as three dimensional parametric modeling software, our mechanical engineers match Sharp's equipment with your operational requirements to maximize packaging speed and uptime. Our CAM (Computer Aided Manufacturing) operations assure an optimal packaging solution for your business.

Streamline communications

Our software engineers have over 30 years of experience developing custom machine software for many types of applications in a wide variety of industries. Packaging operations are completely integrated through our software systems, which streamline PLC, PC, and printer communication. As a result, you have maximum flexibility to revise operations and review real-time results.

Financing and Leasing

Sharp Packaging Systems provides financing and lease options for new and used equipment. These packages are designed to help generate a positive cash flow immediately after equipment installation.



Thermal Transfer Ribbon

Sharp thermal transfer ribbons offer consistent high grade resolution and clear printing for creating superior images at high speeds.





Poly Bags • Bagging Equipment www.SharpPackaging.com

Markets

Aerospace Fasteners Hardware Novelty Candy Jewelry Automotive Electronics Food Hobby Medical Parts Fulfillment Beauty Eyewear Injection Molding Military Retail

Machine Specifications

Dimensions —Height x Depth	Weight	Air	Rate
Base MAX 12" Machine 45.3" wide x 39.7" long With (I) Imprinter 40.1" to 46.3" high	293 lb / 133 kg	80 psi 5 scfm 5.5 bar	50 bags/min ¹
Base MAX 20" Machine 52.6" wide x 49.8" long With (I) Imprinter 39.8" to 45.9" high	348 lb / 158 kg		

Packaging Specifications

2" - 20" / 5 cm - 50.8 cmBag Width Range Bag Length Range 3.5" - 32" / 6.5 cm - 81 cm

1 mil – 4 mil / 25 microns – 100 microns Film Gauge Range

Roll Diameter 10", 14", or fan folded in box²

Printing Cycle Rates (I) Imprinter end of cycle: 50 bags/min

Bag Styles

E-Z Bags®

- General Purpose LDPE
- Xtreme Poly (XP)
- Ultra
- HD Mailer
- SPHD High Density Polyethylene
- Polypropylene
- Sharp's Military Specification Film
- Gamma Patient
- Metalized Barrier Film • Electric Static Discharge (ESD)
- Modified Atmospheric Packaging (MAP) • Non-Scratch Film
- E-Z Stat[™] (Anti-Static)
- Vapor Corrosive Inhibitor (VCI)

Printer Module Specifications

Printing Capabilities

Full downloadable font support to Windows® TrueType® (including multiple languages and Unicode support); Fixed, variable and merged text fields; Flexible date/time formats; Flexible shift code formats; Auto best before date calculations and concession management; Auto incrementing/decrementing text, counters and bar codes; Multiple graphic formats supported (up to maximum print area); Link fields to databases; Scalable text and text blocks

Thermal transfer, directly onto surface of bag **Print Method**

Print Speeds 20"/second

Print Resolution 300 dpi (12 dot/mm)

Print Area (max.) 4.2" (107 mm) wide x 7.9" (200 mm) long

EAN 8, EAN 13, UPC-A, UPC-E, Code 39, EAN 128, Bar codes

Code 128, ITF, RSS (including 2D composite codes);

others available upon request

Operator Interface Built into bagger HMI, WYSIWYG print preview,

Full on-board diagnostics

Nominal Ribbon Waste

Between Successive Prints 0.002" (0.5 mm)

Radial ribbon save, interleaved ribbon save, **Ribbon Saving Features**

intermittent ribbon save

90 - 264V**Power Supply**

Air Supply 6 Bar. 90 psi, 1.0ml/cycle (max), supplied by bagger

Material, gauge, and size of package, along with weight and size of product, will cause rate to vary. ²Fan folded bags in a box require the use of the Box Unwind Module.

MAX 12[™] & MAX 20[™]

Continuous Roll Bagging System

New machines add thermal transfer printer, onboard 12.1" PCs, Allen-Bradley PLC



Sharp's E-Z Bags® feed through the machine, are opened, filled with product, then sealed


■ **Technology advancements** include HMI, a networkable touchscreen PC running Windows® embedded plus an Allen-Bradley PLC

■ Faster, with huge gains in throughput

- Printing is 50% faster than other printers
- Reduced cycle times with the lightweight aluminum jaw
- Quick realignment with heavy duty drive fingers

Cost savings

- No queuing reduces scrap and material cost with moveable printing head
- Thermal ribbon usage reduced as much as 90% with simple adjustments
- Long lasting, constantly heated sealing mechanism
- Off-the-shelf parts





"The power and flexibility of our new packaging systems are at a level that has never been seen before in the pre-opened industry. Our focus throughout the design process was to exceed industry demands regarding overall equipment effectiveness (OEE) and integrated data sharing. The bottom line is that Sharp's customers will have quicker installations and higher throughput, and they will know more about their packaging process in real time."

- Jeramy Williams, Director of Engineering

Faster Printing

- Optional Videojet DataFlex® Plus thermal transfer printer for bar codes, graphics and alphanumeric fonts directly onto the package
- At least 50% faster than printers used by other manufacturers, increasing throughput dramatically
- Set moveable printing head to precise positions, based on package size, to print bags in order, eliminating queuing and reducing scrap and material cost
- Reduce thermal ribbon usage as much as 90% with reduced spacing between impressions, printing with alternative registrations, and adjusting impression placements to increase ribbon usage

Cutting Edge Technology

- Include HMI, a networkable touchscreen PC running Windows® embedded plus an Allen-Bradley PLC
- Touchscreen is a 12.1" TFT (thin film transistor) technology, including a PC with Windows®
- Run Windows labeling software, create labels on the PC, save, then add it to a particular job, so the label format is saved as part of the job
- Includes a high speed counter, pulse train output and network capabilities

More Efficient Operation

- Jaw is aluminum, resulting in less mass, lower inertia, faster movement, and decreased cycle times
- Heavy duty drive fingers don't bend even with tugging at bags, so no need to realign
- The proximity sensor is inside the jaw, protecting the magnet field and improving operation in dirty environments
- The constantly heated sealing mechanism offers a longer life than impulse mechanisms

- Controls for the printer are viewed directly on the bagger HMI, so it's not necessary to manage multiple monitors or displays for the bagger and printing system
- Control, recall stored labels or even create labels directly on the single HMI
- Includes detailed ribbon consumption tools with a gauge that displays how much ribbon remains

Versatility in Loading

- Entire machine moves up or down, adjusting to a wide range of heights
- 90° rotation capabilities for horizontal loading for heavy or stuffable products

Access Data Anywhere

- HMI, printer, and PLC can be networked, so they can be accessed at any time from almost anywhere
- Use remote label printing, production reporting, and SCADA (supervisory control and data acquisition) control

Easy Maintenance

- Off-the-shelf, nonproprietary parts
- Color touchscreen display provides troubleshooting guidance with exploded view drawings, manufacturer and part numbers, and html help files with hyperlinks to explain any term
- Service manual is completely integrated into the diagnostics





The Experts in Packaging Systems

Engineered Systems | Innovative Machines | Excellent Quality Bags

Flexible Packaging Equipment

MAX 12[™]
MAX 20[™]
MAX 24[™]
SX[™]

Film, Bags, and Ribbon

E-Z Bags®

General Purpose LDPE
Xtreme Poly (XP)
Ultra
HD Mailer
SPHD High Density Polyethylene
Polypropylene
Sharp's Military Specification Film
Gamma Patient
Metalized Barrier Film
Electrostatic Discharge (ESD)
Modified Atmospheric Packaging (MAP)
Non-Scratch Film

Stretch Sleeves

Thermal Imprint Ribbon

E-Z Stat[™] (Anti-Static)

Vapor Corrosive Inhibitor (VCI)

Services

On-site consultations to identify the best system for specific flexible packaging needs

Installation and training

Custom bags

Inventory stocking programs

Artwork

Off-the-shelf parts, available from most maintenance supplies companies

Technical support hotline available

7 a.m. – 7 p.m. Central

Video consultations to resolve maintenance issues

On-site service for equipment

Total Systems Care maintenance agreements

Markets

Aerospace Hardware Automotive Hobby

Beauty Injection Molding

Candy Jewelry

Cleaning Products Linen Services

E-Commerce & PBM Medical
Electronics Military
Eyewear Novelty
Fasteners Parts
Food Retail